





TONDO


| D mm |  kg/m | D mm |  kg/m | D mm |  kg/m |
|---------|--|---------|--|---------|--|
| 3 | 0,060 | 20 | 2,470 | 55 | 18,650 |
| 4 | 0,100 | 22 | 2,990 | 60 | 22,200 |
| 5 | 0,160 | 24 | 3,550 | 65 | 26,050 |
| 6 | 0,230 | 25 | 3,860 | 70 | 30,210 |
| 8 | 0,400 | 26 | 4,170 | 75 | 34,680 |
| 10 | 0,630 | 28 | 4,830 | 80 | 39,460 |
| 11 | 0,760 | 30 | 5,550 | 85 | 44,520 |
| 12 | 0,900 | 32 | 6,310 | 90 | 49,940 |
| 13 | 1,060 | 35 | 7,550 | 95 | 55,640 |
| 14 | 1,230 | 36 | 7,990 | 100 | 61,650 |
| 15 | 1,410 | 38 | 8,900 | 120 | 88,780 |
| 16 | 1,610 | 40 | 9,860 | 150 | 138,720 |
| 17 | 1,810 | 45 | 12,480 | - | - |
| 18 | 2,030 | 50 | 15,410 | - | - |

F.LLI MOLINO S.R.L.

Sede: Zona Industriale Giammoro - 98042 Pace del Mela (ME) - Tel. 090 9384090 • info@molinoinox.it

Filiale: Via Giuseppe La Masa, 39/41 - 90139 Palermo - Tel. 091 321600 • palermo@molinoinox.it

ATTENZIONE: Le caratteristiche tecniche sopra riportate sono puramente indicative e possono subire variazioni da lotto a lotto.